

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 January 2002 (24.01.2002)

PCT

(10) International Publication Number
WO 02/06427 A1

- (51) International Patent Classification⁷: **C10G 65/08**
- (21) International Application Number: **PCT/EP01/07933**
- (22) International Filing Date: **10 July 2001 (10.07.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
00402037.6 **17 July 2000 (17.07.2000)** **EP**
- (71) Applicant (for all designated States except US): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]**; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BENARD, Gerard** [FR/FR]; Route départementale no. 3, F-76650 Petit Couronne (FR). **MOUREAUX, Patrick** [FR/FR]; Route départementale no. 3, F-76650 Petit Couronne (FR).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).**
- Published:**
- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 02/06427 A1

(54) Title: **PROCESS TO PREPARE WATER-WHITE LUBRICANT BASE OIL**

(57) Abstract: Process to prepare a water-white lubricating base oil having a saturates content of more than 90 wt%, a sulphur content of less than 0.03 wt% and a viscosity index of between 80-120 by subjecting a non-water-white hydrocarbon feed having a lower saturates content than the desired saturates content to a hydrogenation step, the hydrogenation step comprising contacting the feed with hydrogen in the presence of a hydrogenation catalyst, wherein the contacting is performed in two steps: (a) contacting the hydrocarbon feed with hydrogen in the presence of a hydrogenation catalyst at a temperature of above 300 °C and at a WSHV of between 0.3 and 2 kg of oil per litre of catalyst per hour, and (b) contacting the intermediate product obtained in step (a) with hydrogen in the presence of a hydrogenation catalyst at a temperature of below 280 °C.

PROCESS TO PREPARE WATER-WHITE LUBRICATING BASE OIL

The invention relates to a process to prepare a water-white lubricating base oil having a saturates content of more than 90 wt%, a sulphur content of less than 0.03 wt% and a viscosity index (VI) of between 80-120 by subjecting a non-water-white hydrocarbon feed having a lower saturates content than the desired saturates content to a hydrogenation step. In a hydrogenation step the main reaction is the hydrogenation of aromatic compounds and any other unsaturated compound to saturate compounds.

Lubricating base oils having the above properties are sometimes referred to as a API Group II base oils as defined in API Publication 1509: Engine Oil Licensing and Certification System, "Appendix E-API Base Oil Inter-changeability Guidelines for Passenger Car Motor Oil and Diesel Engine Oils". These properties are also mentioned in Oil & Gas Journal, Sept. 1, 1997, pages 63-70.

In the above referred to Oil & Gas Journal article various routes to Group-II base oils are described. All of the possible routes will involve at one point a hydrogenation of the aromatics and other unsaturated compounds to obtain a base oil having the desired saturates content. Such a hydrogenation will typically be performed by contacting the feed with hydrogen in the presence of a hydrogenation catalyst, typically a Group VIII metal supported catalyst.

US-A-5935416 describes a process to prepare API Group II base oils, wherein the above to referred hydrogenation step is performed as a so-called cold (mild) hydrofinishing step at a temperature of between 230 and 300 °C. The disclosed catalyst used in the

hydrofinishing step is a catalyst containing Group VIB metals and a non-noble Group VIII metal.

WO-A-9802502 discloses a process to prepare API Group II base oils, wherein the hydrogenation process step is performed using a hydrogenation catalyst comprising a platinum/palladium alloy. The illustrated reaction temperature of the hydrogenation was 232 °C.

GB-A-1381004 discloses a process to prepare a base oil by contacting a feed with a nickel-tungsten on alumina catalyst at temperature of between 360 and 410 °C and subsequently contacting the effluent of said step with a catalyst comprising a crystalline aluminosilicate faujasite and palladium at a temperature of between 230 and 370 °C. According to this publication hydrogenation and desulphurisation takes place in the first step and conversion of polycyclic naphthenes and isomerisation of paraffins takes place in the second step. This second step cannot be considered to be a hydrogenation step in view of the conversion reactions taking place in this step as catalysed by the crystalline aluminosilicate faujasite.

GB-A-1333826 discloses a hydrogenation step in a process to prepare base oils. In Example 1 of this publication a three-stage hydrogenation process is illustrated using a nickel on Kieselguhr catalyst, wherein the reaction temperature was 221 °C in the first stage, 232 °C in the second stage and 260 °C in the third stage. The increased severity of the hydrogenation conditions was necessary, according to this publication, to improve the colour.

Applicants have found it almost impossible to prepare in a practical manner water-white Group II base oils, especially having a saturates content of more than 95 wt% and up to 99 wt%, and especially starting from the more difficult feeds containing higher sulphur and/or nitrogen

5 levels. Either coloured Group II base oils or water-white products having a saturates content of less than 90 wt% were prepared. With a practical manner is here meant a process having an acceptable capacity and/or having an acceptable reactor volume.

10 Water-white base oils are desirable because, for example, it ensures the absence of heavy polyaromatics and other harmful species which are detrimental to the product quality, such as for example the oxidation stability. The colour is suitably expressed by means of Colour Saybolt. Preferably the base oil has a Colour Saybolt of above 20 and more preferably above 25. The method of determining Colour Saybolt is described in ASTM D-156 method.

15 It is the object of the present invention to provide a hydrogenation process wherein a water-white base oil having the desired properties can be obtained.

This object is achieved with the following process.

20 Process to prepare a water-white lubricating base oil having a saturates content of more than 90 wt%, a sulphur content of less than 0.03 wt% and a viscosity index of between 80-120 by subjecting a non-water-white hydrocarbon feed having a lower saturates content than the desired saturates content to a hydrogenation step, the hydrogenation step comprising contacting the feed with hydrogen in the presence of a hydrogenation catalyst, wherein the contacting is performed in two steps:

30 (a) contacting the hydrocarbon feed with hydrogen in the presence of a hydrogenation catalyst at a temperature of above 300 °C and at a WSHV of between 0.3 and 2 kg of oil per litre of catalyst per hour, and

35 (b) contacting the intermediate product obtained in step (a) with hydrogen in the presence of a hydrogenation catalyst at a temperature of below 280 °C.

It has been found that with the hydrogenation process according the invention water-white lubricating base oils can be prepared having a high saturates content.

5 The hydrocarbon feed which is used in step (a) may be obtained from various sources. A most common source of the hydrocarbon feed to be used in step (a) is a hydrocarbon feed which in turn is obtained starting from a vacuum distillate or a de-asphalted vacuum residue. These vacuum distillates are obtained by first distilling
10 a petroleum crude feedstock at atmospheric conditions wherein a residue is obtained, which residue is subsequently distilled at reduced pressure obtaining vacuum distillates and a vacuum residue. From the vacuum residue asphalt's are removed in a de-asphalting unit,
15 thereby obtaining a de-asphalted vacuum residue. Part of the aromatics are removed from the vacuum distillate or de-asphalted vacuum residue by means of solvent extraction. In an optional subsequent step wax is removed from the solvent extracted product to obtain the
20 hydrocarbon feed which can be used in step (a). Typically the wax is removed by solvent dewaxing. Optionally wax is removed by means of catalytic dewaxing or isodewaxing.

Optionally the solvent refined product as described above is first subjected to a combined
25 hydrosulphurisation (HDS) and/or hydrodenitrogenation (HDN) step before being used as hydrocarbon feed of step (a). This is advantageous when the solvent refined intermediate product contains high levels of sulphur and/or nitrogen.

30 The feed of step (a) may also be prepared by processes starting from a vacuum distillate or de-asphalted vacuum residue involving a hydrodesulphurisation (HDS) and/or hydrodenitrogenation (HDN) step followed by a hydrocracking step and optionally a

catalytic dewaxing or isodewaxing step as known to one skilled in the art.

Another source of the hydrocarbon feed to step (a) is the product obtained by catalytic dewaxing or isodewaxing a feed containing a high fraction, preferably more than 50 wt%, of wax. Examples of such waxy feeds are slack wax and synthetic waxes as obtained in a Fischer-Tropsch process. Another example of a waxy feed is the high boiling fraction of a hydrocracker process, which process primarily prepares lower boiling middle distillates. Examples of a suitable catalytic dewaxing or isodewaxing processes are described in WO-A-200029511 and EP-A-536325.

The product obtained in the hydrogenation process according to the present invention can be further treated, for example in a clay treating process or contacting with active carbon, as for example described in US-A-4795546 and EP-A-712922, in order to improve the stability of the base oil.

If wax is still present in the feed to step (a) a dewaxing step may be performed on the product of the process according the invention in order to meet any pour point specification. This dewaxing process may be a solvent dewaxing process or catalytic dewaxing or isodewaxing process as known to one skilled in the art.

It has been found that the hydrogenation process according the present invention is particularly suitable when preparing the desired base oils starting from the more difficult feeds, sometimes referred to as refractory feeds, which feeds are characterised by a relatively high sulphur, nitrogen and/or aromatics content and/or a darkish colour. Especially when preparing base oils having a very high saturates content of more than 95 wt%, more especially more than 98 wt%, it has been found that when starting from these more difficult feeds water-white

base oils were difficult to prepare with the state of the art processes.

5 The aromatics content of the feed to step (a) can be between 10% and 65 wt%. The more difficult feed may contain between 35-65 wt% aromatics. The sulphur content can be above 0.03 wt% to even values up to and exceeding 3 wt%. The nitrogen content can be above 1000 ppmw to even values up to and exceeding 2000 ppmw. Suitably the sulphur content is lower than 0.03 wt% and more
10 preferably lower than 1000 ppmw sulphur. Suitably the nitrogen content will be lower than 100 ppmw and more preferably lower than 50 ppmw nitrogen.

15 The colour of the feed to step (a) will be non-white. The invention is especially advantageous when starting from very coloured hydrocarbon feeds to step (a). The colour of the feed will then be such that it cannot be expressed anymore by means of Saybolt Colour. When expressed in terms of "ASTM colour" as described in ASTM D-1500 method, the colour of such a feed is higher
20 than 0.5. The more difficult feed will have a colour of more than 3 and especially 4 or above.

25 The hydrogenation catalyst is suitably a supported catalyst comprising a dispersed Group VIII metal. Possible Group VIII metals are cobalt, nickel, palladium and platinum. Cobalt and nickel containing catalysts may also comprise a Group VIB metal, suitably molybdenum and tungsten.

30 Suitable carrier or support materials are amorphous refractory oxides. Examples of suitable amorphous refractory oxides include inorganic oxides, such as alumina, silica, titania, zirconia, boria, silica-alumina, fluorided alumina, fluorided silica-alumina and mixtures of two or more of these.

35 Suitable hydrogenation catalysts include those catalysts comprising as one or more of nickel (Ni) and

5 cobalt (Co) in an amount of from 1 to 25 percent by weight (%wt), preferably 2 to 15 %wt, calculated as element relative to total weight of catalyst and as the Group VIB metal component one or more of in an amount of from 5 to 30 %wt, preferably 10 to 25 %wt, calculated as element relative to total weight of catalyst. Examples of suitable nickel-molybdenum containing catalyst are KF-847 and KF-8010 (AKZO Nobel) M-8-24 and M-8-25 (BASF), and C-424, DN-190, HDS-3 and HDS-4 (Criterion). Examples of 10 suitable nickel-tungsten containing catalysts are NI-4342 and NI-4352 (Engelhard), C-454 (Criterion). Examples of suitable cobalt-molybdenum containing catalysts are KF-330 (AKZO-Nobel), HDS-22 (Criterion) and HPC-601 (Engelhard).

15 Suitable hydrogenation catalysts have a good hydrogenation performance and are less sensitive for sulphur and/or nitrogen which may be present in the feed. When processing sulphur free feeds a pure nickel containing catalyst might be used. For hydrocracked 20 feeds, especially containing a low amount of sulphur of between 50 and 1000 ppmw, preferably platinum containing and more preferably platinum and palladium containing catalysts are used in steps (a) and optionally in step (b). Especially suitable when processing the above 25 referred to non-white feeds, which may contain high levels of sulphur and/or nitrogen, such as for example the refractory feeds as described above, are the platinum/palladium containing catalysts. More preferably such catalysts are used in both step (a) and step (b).

30 The catalyst of step (a) and (b) are preferably the same. The total amount of these noble Group VIII metal component(s) present on the catalyst is suitably from 0.1 to 10 %wt, preferably 0.2 to 5 %wt, which weight percentage indicates the amount of metal (calculated as 35 element) relative to total weight of catalyst.

Preferred supports for these palladium and/or platinum containing catalysts are amorphous silica-alumina, whereby more preferably the silica-alumina comprises from 2 to 75 %wt of alumina. Examples of suitable silica-alumina carriers are disclosed in WO-A-9410263. A preferred catalyst comprises an alloy of palladium and platinum preferably supported on an amorphous silica-alumina carrier of which the commercially available catalyst C-624 of Criterion Catalyst Company (Houston, TX) is an example. These catalyst are advantageous because they deactivate less when the sulphur content of the feed is relatively high.

Step (a) is performed at a temperature of above 300 °C. In this step the main part of the hydrogenation of the aromatic compounds take place, in particular the hydrogenation of mono-aromatics. The temperature will suitably not exceed 400 °C and preferably is in the range of from between 300 and 380 °C. The operating hydrogen pressure may range from 10 to 250 bar. It has been found that improved results are obtained at higher pressures, preferably above 100 bar and more preferably between 120 and 250 bar. The WHSV (Weight hourly space velocity) ranges from 0.3 to 2 kg of oil per litre of catalyst per hour (kg/l.h). The actual operating conditions will depend on the required degree of saturation and the aromatics content in the feed and can be easily determined by one skilled in the art given the above guidelines.

Step (b) is performed at a temperature of below 280 °C and more preferably below 250 °C. In this step the colour improvement takes place. The minimum temperature is suitably above 100 °C. The operating hydrogen pressure may range from 10 to 250 bar. It has been found that improved results with respect to colour are obtained at higher pressures, preferably above 100 bar and more

preferably between 120 and 250 bar. The WHSV preferably ranges from 0.3 to 3 kg of oil per litre of catalyst per hour (kg/l.h) and more preferably between 1 and 1.5 kg/l.h. The actual operating conditions will depend on the required colour and the colour of the feed and can be easily determined by one skilled in the art given the above guidelines.

Step (a) and step (b) are preferably performed at the same hydrogen partial pressure for practical reasons. The hydrogenation catalyst is preferably present in a packed bed reactor. Step (a) and Step (b) can be performed in a continuous operation in two separate sequentially arranged reactors, suitably with means to cool the intermediate product before it is used in step (b). Suitable cooling means are indirect heat exchangers, for example tube/shell heat exchangers. It is also possible to perform step (a) and (b) in one and the same reactor in a so-called blocked out operation, wherein first the feed is fed to the reactor under the conditions of step (a) and second the collected intermediate product is fed to the same reactor under the conditions of step (b). The latter procedure is advantageous with respect to the number of required hydrogenation reactors when a two step hydrogenation according to the invention is only occasionally required.

Optionally, for example when the required temperature difference between steps (a) and (b) is not too big, step (a) and step (b) can be performed in a stacked bed column. Between the catalyst beds means to reduce the temperature, for example by means of a quench, will be present.

The invention will be illustrated by the following non-limiting examples.

Example 1

A feed having the properties as stated in Table 1 was obtained by first hydrocracking a vacuum distillate and subsequently catalytic dewaxing the hydrocracked product.

Table 1

Property	Feed to step (a)
saturates (wt%) (ASTM D 2007)	90
polars (wt%) (ASTM D 2007)	10
aromatics (wt%) (ASTM D 2007)	10
sulphur (mg/kg)	132
nitrogen (mg/kg)	2
Viscosity Index	98
viscosity at 100 °C (cSt)	8.8
viscosity at 40 °C (cSt)	2.446
pour point (°C)	-25
colour ASTM	4

5 The feed described in Table 1 was hydrogenated by contacting with a platinum/palladium catalyst of the Criterion Catalyst Company, namely the C-624 catalyst at a hydrogen partial pressure of 200 bar and a WSHV of 1 kg/l.hr at 370 °C and at a recycle gas rate of 1500 Nl/kg. The effluent of this reaction was hydrogenated under the same conditions but now at 230 °C. The resultant base oil had a saturates content of 98.2 wt% and a Colour Saybolt of +28, a sulphur content of 6.6 mg/kg and a VI of 106.

15 Example 1 illustrates that with the process of the invention Group II base oils can be prepared having a very high saturates content and an excellent colour.

Example 2

20 Example 1 was repeated except that the pressure was 140 bar and the temperature in the first hydrogenation step was 345 °C. The resultant base oil had a saturates

content of 95.6 wt% and a Colour Saybolt of +24, a sulphur content of 6.2 mg/kg and a VI of 102.

Comparative Experiment A

5 A feed, obtained by first hydrocracking a base oil distillate fraction and subsequently catalytic dewaxing, contained about 21 wt% aromatics. This feed was hydrogenated by contacting with a platinum/palladium catalyst of the Criterion Catalyst Company, namely the C-624 catalyst at a hydrogen partial pressure of 140 bar and a WSHV of 1 kg/1.hr and at a recycle gas rate of 1500 Nl/kg at different temperatures. See Table 2 for results at the different temperatures.

Table 2

Temperature (°C)	Colour of hydrogenated product	Aromatic content SMS 2660 (%m)
220	Colour Saybolt 23	16.2
250	Colour Saybolt 20	14.0
280	Colour Saybolt 15	11.8
310	ASTM 1-(*)	8.1

(*) colour too dark to be expressed in Colour Saybolt. Instead the colour is expressed in ASTM D-1500 method having the value 1-.

15 The results in Table 2 illustrate that good colour can be obtained at low temperatures. However the desired Group II base oil is not obtained because the aromatics content is too high. If the degree of hydrogenation is increased by raising the temperature the desired water-white colour is not obtained.

C L A I M S

1. Process to prepare a water-white lubricating base oil having a saturates content of more than 90 wt%, a sulphur content of less than 0.03 wt% and a viscosity index of between 80-120 by subjecting a non-water-white hydrocarbon feed having a lower saturates content than the desired saturates content to a hydrogenation step, the hydrogenation step comprising contacting the feed with hydrogen in the presence of a hydrogenation catalyst, wherein the contacting is performed in two steps:
- (a) contacting the hydrocarbon feed with hydrogen in the presence of a hydrogenation catalyst at a temperature of above 300 °C and at a WSHV of between 0.3 and 2 kg of oil per litre of catalyst per hour, and
- (b) contacting the intermediate product obtained in step (a) with hydrogen in the presence of a hydrogenation catalyst at a temperature of below 280 °C.
2. Process according to claim 1, wherein the hydrogenation catalyst is a supported catalyst comprising a dispersed Group VIII metal.
3. Process according to claim 2, wherein the Group VIII metal of the hydrogenation catalyst used in step (a) and in step (b) is platinum.
4. Process according to claim 3, wherein the catalyst also comprises dispersed palladium.
5. Process according to claim 4, wherein the catalyst comprises an alloy of platinum and palladium and wherein the support is an amorphous silica-alumina.
6. Process according to any one of claims 1-5, wherein the feed has an ASTM-D-1500 colour of more than 3.

7. Process according to any one of claims 1-6, wherein the hydrogen pressure in steps (a) and (b) is between 120 and 250 bar.
- 5 8. Process according to any one of claims 1-7, wherein the temperature in step (a) is between 300 and 380 °C.
9. Process according to any one of claims 1-8, wherein the temperature in step (b) is between 100 and 250 °C.
- 10 10. Process according to any one of claims 1-9, wherein the water-white base oil has a Colour Saybolt of above 20, preferably above 25.
11. Process according to any one of claims 1-10, wherein the saturates content of the base oil is above 95 wt%, preferably above 98 wt%.
- 15 12. Process according to any one of claims 1-11, wherein the feed to step (a) contains between 35 and 65 wt% aromatics.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 01/07933

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C10G65/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 935 416 A (LETA DANIEL P ET AL) 10 August 1999 (1999-08-10) cited in the application column 2, line 23 -column 3, line 63 column 4, line 16-22 column 5, line 15-20 column 5, line 60 -column 6, line 20 column 6, line 65 -column 7, line 7 column 8, line 13-28; claims 1-3,7,9; example 7	1,2,6-11
X	WO 98 02502 A (CHEVRON USA INC) 22 January 1998 (1998-01-22) cited in the application page 3, line 14-32; claims 1,5,17; examples 3-5,7,8; tables III,VI -/--	1-6,8-12

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

14 December 2001

Date of mailing of the international search report

20/12/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Kazemi, P

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 01/07933

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 1 381 004 A (EXXON RESEARCH ENGINEERING CO) 22 January 1975 (1975-01-22) cited in the application page 1, line 53-80 page 3, line 89-130; examples 1-3; tables I-VII	1,2,7-12
X	GB 1 333 826 A (EXXON RESEARCH ENGINEERING CO) 17 October 1973 (1973-10-17) cited in the application page 6, line 33-99; examples 1-3; tables VI,VII	1,2,7-12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/EP 01/07933

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5935416	A	10-08-1999	US 5976353 A	02-11-1999
			AU 2676699 A	30-08-1999
			EP 1054940 A1	29-11-2000
			WO 9941338 A1	19-08-1999
			AU 718741 B2	20-04-2000
			AU 3641997 A	21-01-1998
			CA 2257918 A1	08-01-1998
			EP 0907697 A1	14-04-1999
			WO 9800479 A1	08-01-1998
			US 6325918 B1	04-12-2001
			US 5911874 A	15-06-1999
WO 9802502	A	22-01-1998	AU 724570 B2	28-09-2000
			AU 3716597 A	09-02-1998
			BR 9710321 A	17-08-1999
			CA 2260104 A1	22-01-1998
			CN 1225662 A	11-08-1999
			CZ 9900097 A3	14-04-1999
			EP 0912659 A1	06-05-1999
			HU 0003145 A2	28-02-2001
			PL 331039 A1	21-06-1999
			TR 9900098 T2	21-04-1999
			WO 9802502 A1	22-01-1998
			US 6264826 B1	24-07-2001
			US 5993644 A	30-11-1999
GB 1381004	A	22-01-1975	NONE	
GB 1333826	A	17-10-1973	CA 958355 A1	26-11-1974
			FR 2080537 A5	19-11-1971

THIS PAGE LEFT BLANK